

SPEEDLINE TRUCK Accessories

Truck
speedline

Exclusive accessories for forged light alloy wheels for commercial vehicles and buses.



1. Shank nuts and nut covers

We recommend to base any research on the vehicle type and axle version installed on the vehicle type to determine further on the required wheel type and shank nut. Further technical details are available on the data sheets of each mentioned SPEEDLINE TRUCK wheel.






Size	Picture	Fitting wheel sizes	Fitting SPEEDLINE TRUCK wheels	Denomination	Article code	Single/Twin fitment	Technical details	Remarks
M18x1.5		17.5x6.75"	SLT 2901 A	SLT-987	683.6090.005	S	Dacromet coating	Recommended torque: 400 Nm
	SLT-988			683.6090.006	T			
M20x1.5		17.5x6.75"	SLT 2901 B, SLT 2911 B	SLT-989	683.6090.009	S	Delta-Protpekt coating	Recommended torque: 500 Nm
	SLT-990			683.6090.008	T			
M22x1.5		19.5x7.50", 19.5x14", 22.5x7.50", 8.25", 9.00", 11.75" (ET0/45/120/135), 13"	SLT 3087 B, SLT 3598 B, SLT 3211 B, SLT 2900 B, SLT 2887 B, SLT 2907 B, SLT 2899 B, SLT 3099 B, SLT 3774 B, SLT 2888 B, SLT 2898 B, SLT 3063 B, SLT 3187 B	SLT-979	683.6090.001	S	Delta-Protpekt coating	Recommended torque: 600 – 680 Nm
	SLT-910			683.6090.002	T			
7/8"11 BSF		8.25", 9.00", 11.75" (ET 135) only for use on Scania	SLT 2900 B, SLT 2887 B, SLT 2907 B, SLT 3063 B	SLT-983	683.6090.003	S	Delta-Protpekt coating	Recommended torque: 600 – 680 Nm
	SLT-984			683.6090.004	T			
Nut cover plastic plated		For all wheels in 22.5"	all	SLT-991	683.6280.001	all	Plastic, chromed	Fitting for 32 mm shank nuts only

Light wheels for heavy weights



SPEEDLINE TRUCK Accessories

2. Valves and valve extensions


SPEEDLINE TRUCK valves are made especially for forged light metal wheels. The below mentioned recommended torque values are only valid for original SPEEDLINE TRUCK valves. For any similar ETRTO valve type mentioned below in alternative please, refer to the torque values recommended by the respective producer.

Type	Picture	Fitting wheel sizes	Fitting SPEEDLINE TRUCK wheels	Denomination	Article code	Technical details	Remarks
SLT-003		17.5x6.75", 22.5x8.25", 22.5x9.00"	SLT 2901, SLT 2911, SLT 2900, SLT 2897, SLT 2907	SLT-003	683.6010.003	TRA type: TR 553	Recommended torque: 3 - 5 Nm
						DIN 54MS	
SLT-004		17.5x6.75"	SLT 2891, SLT 3086	SLT-004	683.6010.004	TRA type: TR 544C	Recommended torque: 3 - 5 Nm
						ETRTO type: V3.22.1	
SLT-020		19.5x7.50", 22.5x11.75", ET0, 22.5x13.00"	SLT 3087, SLT 2889, SLT 3099, SLT 3187	SLT-020	680.6010.020	TRA type: TR 543C	Recommended torque: 3 - 5 Nm
						ETRTO type: V3.22.1	
SLT-021		19.5x14.00", ET 120, 22.5x11.75", ET 0, ET 45, ET 120, ET 135	SLT 2899, SLT 2888, SLT 2898, SLT 3063, SLT 3598, SLT 3774	SLT-021	680.6010.021	TRA type: TR 542	Recommended torque: 3 - 5 Nm
						ETRTO type: V3.20.1	
SLT-022		22.5x7.50", 22.5x9.00"	SLT 3201, SLT 3211, SLT 2887	SLT-022	683.6010.022	DIN 70MS-07	Recommended torque: 3 - 5 Nm

Valve extensions

Extensions base		45° for twin fitment	For all sizes in twin fitment, at external wheel position	SLT-007	683.0040.007	Material: brass	-
Valve extensions		115 mm length	SLT 2901, SLT 2911, SLT 3086, SLT 3087	SLT-008	683.0040.008	Material: techno- polymer	-
		150 mm length	SLT 2900, SLT 3201, SLT 3211, SLT 2887, SLT 2897, SLT 2907	SLT-009	683.0040.009		

3. Other Tooling

Type	Picture	Fitting wheel sizes	Fitting SPEEDLINE TRUCK wheels	Denomination	Article code	Technical details	Remarks
Measurement gauge for rim horn wear		Fitting for all sizes	Applicable on all SPEEDLINE TRUCK wheels	SLT-001	683.8310.001	Steel body	-

www.speedline-truck.com